



# Desktop Manager

- Multifunctional monochrome system for high quality documents at a speed of up to 52 ppm
- Sophisticated e-BRIDGE technology for flexible solution and network integration
- Large colour LCD touch panel for intuitive and effective system usage
- Equipped with the Toshiba Secure HDD for highest document security standards
- Compliant with ENERGY STAR® criteria thanks to low Energy consumption

**e-STUDIO477s**  
**e-STUDIO527s**



SAP® Printer Vendor Solution





e-STUDIO477s

e-STUDIO527s



<p><b>General</b></p>	<p><b>Print &amp; Copy Speed</b> 47/52 ppm Approx. 35 seconds</p> <p><b>Warm-up Time</b></p> <p><b>Paper Size &amp; Weight</b> Cassette: A5-A4, 64-220 g/m<sup>2</sup> Bypass: A6-A4, 64-250 g/m<sup>2</sup> banner paper (up to 216 x 1321 mm, 80-128 g/m<sup>2</sup>)</p> <p><b>Paper capacity</b> 1 x 530 sheets (Cassette), 100 sheets (Bypass) Maximun 3,160 sheets</p> <p><b>Automatic Duplex</b> A5-A4, 64-220 g/m<sup>2</sup> 500 sheets</p> <p><b>Inner Output Tray</b> 500 sheets</p> <p><b>Controller Type</b> Toshiba e-BRIDGE</p> <p><b>Controler Panel</b> 9" (22.8 cm) colour touch panel LCD</p> <p><b>Memory</b> Toshiba Secure HDD 160GB<sup>1)</sup> HDD / 2GB RAM</p> <p><b>Interface</b> 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN<sup>2)</sup> (IEEE802.11b/g/n)</p> <p><b>Dimension &amp; Weight</b> 522 x 564 x 811 mm (W x D x H), ~ 47 kg</p> <p><b>Starter kit</b> Toner, Drum</p>
<p><b>Print</b></p>	<p><b>Resolution</b> 600 x 600 dpi, 1,200 x 1,200 dpi (1 bit, PS driver only)</p> <p><b>Page Description Language</b> XPS, PCL 6 and PostScript 3 compatible</p> <p><b>Supported Systems</b> Windows 8/7/Vista/XP/Server 2008/ Server 2003 (32/64 bit), Server 2012/ Server 2008R2 (64 bit), Mac OS X 10.4.11-10.8, Citrix, Linux/Unix, Novell NetWare (NDPS), SAP, AS/400</p> <p><b>Print Functions</b> Universal Printer Driver, One-Touch Templates, Driver plug-ins<sup>2)</sup>, Print from USB, Multiple pages per sheet</p>
<p><b>Scan</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi</p> <p><b>Scan Speed</b> 52/40 ipm (monochrome/colour with 300 dpi)</p> <p><b>Document Feeder</b> Simplex: Max 100 sheets, A6-A4, 60-105 g/m<sup>2</sup> Duplex: Max. 100 sheets, A5-A4, 60-105 g/m<sup>2</sup></p> <p><b>Scan Modes</b> Auto-Colour (ACS), Colour, Greyscale, Monochrome</p> <p><b>File Formats</b> JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, Searchable PDF<sup>2)</sup> (and other formats like DOCX, XLSX, RTF, TXT, PDF/A)<sup>2)</sup></p> <p><b>Scan Functions</b> WS scan, Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, SPX/IPX, local), Meta Scan<sup>2)</sup>, Scan to Box (e-filing), WIA, TWAIN</p>
<p><b>Copy</b></p>	<p><b>Resolution</b> Scan: 600 x 600 dpi Print: 600 x 600 dpi</p> <p><b>First Copy Output Time</b> approx. 8 seconds</p> <p><b>Zoom</b> 25-400% (platen), 25-200% (RADF)</p> <p><b>Copy Modes</b> Text, Text/Photo, Photo</p> <p><b>Copy Functions</b> Electronic sort, ID card copy, Edge Erase, 2-in-1 / 4-in-1 mode</p>
<p><b>Fax<sup>2)</sup></b></p>	<p><b>Communication</b> Super G3, G3, Internet Fax T.37</p> <p><b>Transmission Speed</b> Approx. 3 seconds per page</p> <p><b>Compression</b> JBIG, MMR, MR, MH</p> <p><b>Fax Memory</b> 1GB Transmission/Reception</p> <p><b>Network-fax</b> Driver Windows 8/7/Vista/XP/ Server 2008/ Server 2003 (32/64 bit), Server 2012/ Server 2008R2 (64 bit) To shared folders (SMB, FTP, IPX), E-Mail, e-Filing</p>
<p><b>System &amp; Security</b></p>	<p><b>Incoming Fax Routing</b> e-BRIDGE Fleet Management System<sup>2)</sup>, Top Access for remote administration and configuration</p> <p><b>Device Management</b> e-Filing document server for secure storage, document distribution and print on demand (1 public box, 200 user boxes), 12,060 One-Touch Templates for storage of personalised settings or workflows, Scan/fax preview, Rip-while-Print, e-BRIDGE Open Platform<sup>2)</sup>, Job Skip</p> <p><b>System Features</b> Role Based Access, LDAP support, 1,000 department &amp; 10,000 user codes, card reader<sup>2)</sup>, privat print, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler<sup>2)</sup>, IP and MAC address filter, port filter, support of SSL and IPSec<sup>2)</sup> protocols, IEEE802.1x support, IEEE2600.1 compliant<sup>2)</sup>, Scan to Secure PDF</p>

**OPTIONS**

**PAPER FEED UNIT – MY-1046**

530 sheets cassette, A5-A4, 64-220 g/m<sup>2</sup>  
522 x 485 x 136 mm (W x D x H) ~ 7.3 kg

**LARGE CAPACITY FEEDER – KD-1040**

550 sheets (1 cassette), A4, 64-220 g/m<sup>2</sup>  
705 x 758 x 404 (W x D x H) ~ 31 kg

**INNER FINISHER – MJ-1038**

1 tray, 500 sheet capacity  
50-sheets stapling  
A5-A4, 64-104 g/m<sup>2</sup> (stapling mode)  
387 x 566 x 215 mm (W x D x H), ~ 8.3 kg

**OFFLINE STAPLER – MJ-1039**

20 sheets offline stapler, one position

**CASTER – GR-1170**

Stabiliser  
795 x 765 x 132 mm (W x D x H, incl. Stand),  
~ 14.7 kg

**SPACER – GR-1160**

522 x 485 x 136 mm (W x D x H) ~ 5.3 kg

**OTHER OPTIONS**

- DESK – MH-3400
- FAX BOARD – GD-1340EU
- WIRELESS LAN MODULE – GN-1060
- e-BRIDGE ID-GATE – TWN3/4xx
- DATA OVERWRITE ENABLER – GP-1070
- META SCAN ENABLER – GS-1010
- IPsec ENABLER – GP-1070
- UNICODE ENABLER – GS-1007
- e-BRIDGE RE-RITE – GB-1280

Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m<sup>2</sup> if not otherwise mentioned.

<sup>1)</sup> 1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.

<sup>2)</sup> optional



Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2013 TOSHIBA TEC. DS527sGBEMD1305